

A KOHLER COMPANY

Features


- Installs left- or right-handed
- No top track allows easy access into the shower
- Tempered glass ensures maximum safety and durability
- Aluminum components extruded from alloy 6063-T5
- Stainless steel hardware prevents rusting or corrosion
- Anodized aluminum frameless sliding glass doors
- · Adjustable wall jamb allows for out-of-plumb adjustability

Codes/Standards Applicable

Specified model meets or exceeds the following:

ANSI Z97.1 (tempered glass)

STANDARD PIVOT SHOWER DOORS 950C



Colors/Finishes

• NA: None applicable

Specified Model

Model	Application	Glass Texture	Pattern	* Frame Colors/Finishes	
950C-24*	Shower	Hammered	None	□NA	
950C-28*	Shower	Hammered	None	□ NA	
950C-30*	Shower	Hammered	None	□ NA	
950C-32*	Shower	Hammered	None	□ NA	
950C-36*	Shower	Hammered	None	□NA	
* Note: Add appropriate frame color/finish code to the end of the unit model # when ordering					

Technical Information

Model	A (Max / Min width)	B (Height)	C (Walk Through Max)
950C-24*	25" (63.5 cm)/ 23-1/2" (59.7 cm)	64" (162.6 cm)	21-3/16" (53.8 cm)
950C-28*	28-1/2" (72.4 cm)/ 27" (68.6 cm)	64" (162.6 cm)	24-11/16" (62.7 cm)
950C-30*	30-1/2" (77.5 cm)/ 29" (73.7 cm)	64" (162.6 cm)	26-11/16" (67.8 cm)
950C-32*	32-1/2" (82.6 cm)/ 31" (78.7 cm)	64" (162.6 cm)	28-11/16" (72.9 cm)
950C-36*	36" (91.4 cm)/ 34-1/2" (87.6 cm)	64" (162.6 cm)	32-3/16" (81.8 cm)

